

## SÜDWEST Super-Dickschutz Uni

Ref. 130000006437/

Rev. no. 1.5

Revision Date 16.07.2018 Print Date 17.07.2018

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name SÜDWEST Super-Dickschutz Uni

1.2 Relevant identified uses of the substance or mixture and uses advised against

Corrosion inhibitor

Lacquer

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG

Iggelheimer Str. 13

D - 67459 Böhl-Iggelheim Telephone: +49 6324/709-0 Telefax: +49 6324/709-175

www.suedwest.de

E-mail address of person responsible for the SDS

sdb@suedwest.de

European Union

1.4 Emergency

telephone number

European Union

Phone: +44 (0)1235 239 670

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids,

H226: Flammable liquid and vapour.

Category 3

Long-term (chronic) aquatic H411: Toxic to aquatic life with long lasting effects.

hazard, Category 2

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H411 Toxic to aquatic life with long lasting

effects.

Supplemental Hazard

Statements

EUH066 Repeated exposure may cause skin

dryness or cracking.

Precautionary

statements

P102 **Prevention:** 

P210

Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing.

Rinse skin with water or shower.

Disposal:

P501 Contents/container to be disposed of

through approved disposal contractor or

taken to municipal collection point.

#### **Additional Labelling:**

EUH208 Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-

piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2 Mixtures

#### **Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9 01-2119457273-39- XXXX	Asp. Tox.1; H304  The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 10 - < 25
Hydrocarbons, C9- C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9 01-2119471843-32- XXXX	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic3; H412 Note P The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 2,5 - < 5
zinc oxide	1314-13-2 215-222-5 01-2119463881-32- XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	≥ 2,5 - < 5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 01-2119485044-40- XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	≥ 2,5 - < 5
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4- piperidyl sebacate	915-687-0 01-2119491304-40- XXXX	Aquatic Chronic1; H410 Aquatic Acute1; H400 Skin Sens.1; H317	≥ 0,25 - < 0,5
2-Ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1	Repr.2; H361d	≥ 0,1 - < 1

	01-2119979088-21- XXXX		
2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl- 1,3-propanediamine	222417-26-7	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic1; H410 Aquatic Acute1; H400	≥ 0,1 - < 0,25

For explanation of abbreviations see section 16.

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

General advice When symptoms persist or in all cases of doubt seek

medical advice.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical

advice.

Inhalation Move to fresh air in case of accidental inhalation of vapours

or decomposition products. Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial

respiration.

If symptoms persist, call a physician.

Skin contact Take off contaminated clothing and shoes immediately.

Wash skin thoroughly with soap and water or use

recognized skin cleanser.

Do NOT use solvents or thinners. If skin irritation persists, call a physician.

Eye contact In case of eye contact, remove contact lens and rinse

immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Seek medical advice.

Ingestion Rinse mouth with water.

If swallowed, seek medical advice immediately and show

this container or label.

Keep at rest.

Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

No information available.

#### **SECTION 5: FIREFIGHTING MEASURES**

5.1 Extinguishing media

Suitable extinguishing

media

CO2, extinguishing powder or water spray. Fight larger fires

with water spray or alcohol resistantfoam.

Unsuitable extinguishing

media

High volume water jet

Fire may cause evolution of:

5.2 Special hazards arising from the substance or mixture

Carbon monoxide

Carbon dioxide (CO2) Nitrogen oxides (NOx)

Exposure to decomposition products may be a hazard to

health.

Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Fight fire with normal precautions from a reasonable

distance.

Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

6.1 Personal

precautions, protective

equipment and

emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Do not breathe vapour.

Prevent unauthorized access.

6.2 Environmental precautions

The product should not be allowed to enter drains, water

courses or the soil.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Clean with detergents. Avoid solvents. Clean contaminated surface thoroughly.

Dispose of contaminated material as waste according to

item 13.

6.4 Reference to other

Refer to protective measures listed in sections 7 and 8.

### SÜDWEST Super-Dickschutz Uni

#### sections

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling

Advice on safe handling Comply with the statutory regulations on health and safety at

work.

Avoid formation of aerosol.

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour

concentration higher than the occupational exposure limit values.

The product should only be used in areas from which all naked lights and other sources of ignition have been

excluded.

All metal parts of the mixing and processing equipment must

be earthed.

Operators should wear antistatic footwear and clothing. No

sparking tools should be used.

Hygiene measures Do not breathe spray, vapour.

Take off immediately all contaminated clothing. Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

After washing hands, replenish lost skin oil by means of oily

skin ointment.

When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and

containers

Store in original container.

Keep container tightly closed. Never use pressure to empty:

container is not a pressure vessel. Nosmoking.

Prevent unauthorized access.

Containers which are opened must be carefully resealed

and kept upright to prevent leakage. Keep in a well-ventilated place. Protect from frost, heat and sunlight.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic

charge.

Advice on common

storage

Keep away from combustible materials.

Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or

alkaline materials.

**7.3 Specific end use(s)** For further information, see also Technical Data Sheet for

the product.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

#### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should beachieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

#### Individual protection measures, such as personal protective equipment

a) Eye/face protection Safety glasses with side-shields conforming to EN166

b) Skin protection Hand protection

Recommended preventive skin protection

Before starting work, apply water-resistant skincare

preparations to exposed skin areas.

Protective gloves should be worn in case of skin contact

during preparation and application.

Break through time: 480 min Minimum thickness: 0,4 mm

Gloves made of nitrile rubber, e.g. KCL 730 Camatril®

Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-

87-300, kcl-uk@kcl.de), or equivalent.

Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the

specifications of EU Directive 89/686/EEC and the standard

EN 374 derived from it.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

from one producer to the other.

Body Protection Preventive skin protection

Long sleeved clothing

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthehic fiber. All parts of the body should be washed after contact.

c) Respiratory protection When workers are facing concentrations above the

occupational exposure limit values they must use

appropriate certified respirators.

Breathing protection equipment required in inadequately

ventilated places and during spraying.

In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate

respirator.

Combination filter A-P2

Respiratory protection complying with EN 14387.

#### **Environmental exposure controls**

General advice The product should not be allowed to enter drains, water

courses or the soil.

If the product contaminates rivers and lakes or drains

inform respective authorities.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1 Information on basic physical and chemical properties

Appearance liquid

Colour various

Odour characteristic

Odour Threshold No data available

pH not determined

Melting point/freezing point 

No data available

Initial boiling point and

boiling range

No data available

44 °C Flash point

Method: closed cup

Evaporation rate not determined

Flammability (solid, gas) not applicable

Upper explosion limit / Upper flammability limit No data available

Lower explosion limit / Lower flammability limit No data available

Vapour pressure No data available

Vapour density No data available

Density ca. 1,310 g/cm3 (20 °C)

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

not determined

Decomposition

temperature

No data available

Viscosity

Viscosity, dynamic ca. 9,11 mPa.s (20 °C)

Viscosity, kinematic No data available

Explosive properties Not explosive

In use may form flammable/explosive vapour-air mixture.

Oxidizing properties Not applicable

9.2 Other information

Self-ignition not auto-flammable

Flow time > 90 s at 20 °C

Cross section: 4 mm

#### **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of

normal use.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid Direct sources of heat.

Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

Decomposition

temperature

No decomposition if stored and applied as directed.

No data available

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

**Acute toxicity Product:** 

Acute oral toxicity Based on available data, the classification criteria are

not met.

Based on available data, the classification criteria are Acute inhalation toxicity

not met.

Acute dermal toxicity Based on available data, the classification criteria are

not met.

Skin corrosion/irritation

**Product:** 

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Repeated exposure may cause skin dryness or cracking.

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Repeated exposure may cause skin dryness or cracking.

### 2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-

1,3-propanediamine:

Species Rabbit

Method OECD Test Guideline 404
Causes skin irritation.

#### Serious eye damage/eye irritation

**Product:** 

Based on available data, the classification criteria are

not met.

#### **Components:**

# 2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:

Species Rabbit

Method OECD Test Guideline 405 Causes serious eye damage.

#### Respiratory or skin sensitisation

**Product:** 

Based on available data, the classification criteria are

not met.

#### **Components:**

## Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Method OECD Test Guideline 406

May cause an allergic skin reaction.

#### Germ cell mutagenicity

Product:

Genotoxicity in vitro Based on available data, the classification criteria are

not met.

#### Carcinogenicity

**Product:** 

Based on available data, the classification criteria are

not met.

#### Reproductive toxicity

**Product:** 

Effects on fertility Based on available data, the classification criteria are

### SÜDWEST Super-Dickschutz Uni

not met.

Developmental Toxicity Based on available data, the classification criteria are

not met.

#### **Components:**

#### 2-Ethylhexanoic acid, zirconium salt:

Developmental Toxicity Suspected of damaging the unborn child.

#### STOT - single exposure

**Product:** 

Based on available data, the classification criteria are

not met.

#### **Components:**

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment May cause drowsiness or dizziness.

#### STOT - repeated exposure

**Product:** 

Based on available data, the classification criteria are

not met.

#### **Aspiration toxicity**

#### **Product:**

Based on available data, the classification criteria are not met.

#### **Components:**

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

### Experience with human exposure

#### **Product:**

General Information Exposure to component solvent vapours concentration

in excess of the stated occupational exposure limit may

result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatique, muscular weakness.

drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the

resorption of substances.

Solvent sprays can cause irritation and reversible

damage to the eye.

Further information **Product**:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

**Product:** 

Toxicity to fish No data available

#### **Components:**

zinc oxide:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 0,5 mg/l

Exposure time: 96 h Test Type: static test

M-Factor (Short-term (acute) aquatic hazard)

1

Toxicity to fish (Chronic

toxicity)

NOEC: 0,08 mg/l Exposure time: 21 d

Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Long-term (chronic) aquatic hazard)

1

#### trizinc bis(orthophosphate):

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,33 -

6,06 mg/l

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 2,34 mg/l

Exposure time: 48 h

Toxicity to algae EC50 (Scenedesmus capricornutum (fresh water

algae)): 0,32 mg/l Exposure time: 72 h

1

M-Factor (Short-term (acute) aquatic hazard)

M-Factor (Long-term 1 (chronic) aquatic hazard)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate :

Toxicity to fish LC50 (Lepomis macrochirus (Bluegill sunfish)): 0,97 mg/l

Exposure time: 96 h

Toxicity to daphnia and EC50 (Daphnia magna (Water flea)): 20 mg/l

other aquatic invertebrates Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae EC50 (Desmodesmus subspicatus (green algae)): 1,68

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Short-term 1

(acute) aquatic hazard)

Toxicity to bacteria EC50 (activated sludge): > 100 mg/l

1

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

NOEC: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine :

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,89 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 202

M-Factor (Short-term (acute) aquatic hazard)

12.2 Persistence and degradability

**Product:** 

Biodegradability No data available

**Components:** 

### SÜDWEST Super-Dickschutz Uni

#### Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Biodegradability Test Type: aerobic

Result: not rapidly degradable

Biodegradation: 38 % Exposure time: 28 d

Method: OECD Test Guideline 301F

#### 2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:

Biodegradability Result: not rapidly degradable

Method: OECD Test Guideline 301B

#### 12.3 Bioaccumulative potential

#### **Product:**

Bioaccumulation No data available

#### **Components:**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics :

Partition coefficient: nlog Pow: 4

octanol/water

zinc oxide:

Bioaccumulation Bioaccumulation is unlikely.

#### trizinc bis(orthophosphate):

Bioaccumulation Does not bioaccumulate.

#### Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Bioaccumulation Bioaccumulation is unlikely.

#### 12.4 Mobility in soil

#### **Product:**

No data available Mobility

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment This substance/mixture contains no components

> considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative

(vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

### SÜDWEST Super-Dickschutz Uni

#### **Product:**

Additional ecological information

Do not use in the direct vicinity of bodies of water. Do not allow the agent or any product residues to enter into waters, the soil or the sewage system. Even small quantities emptied into the soil can affect the quality of drinking water. Toxic to aquatic life with long lasting effects.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of

any waste.

When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and

**Demolition Waste**"

Partial and residual quantities can be reused.

Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a

local waste disposal site.

Contaminated packaging Packaging that is not properly emptied must be disposed of

as the unused product.

Empty packaging should be recycled through disposal

systems.

Waste key for the unused product

08 01 11\* Paint and varnish waste containing organic

solvents or other dangerous substances

(\*) hazardous waste in terms of the European directive

91/689/EEC

#### **SECTION 14: TRANSPORT INFORMATION**

14.1 UN number

**ADR** 1263

**IMDG** 1263

**IATA** 1263

14.2 UN proper shipping name

**ADR** PAINT

IMDG PAINT

(zinc oxide, trizinc bis(orthophosphate))

**IATA** Paint

14.3 Transport hazard class(es)

ADR 3

IMDG 3

IATA 3

14.4 Packing group

**ADR** 

Packing group III

Classification Code F1

Hazard Identification 30

Number

Labels 3

Tunnel restriction code (D/E)

**IMDG** 

Packaging group III

Labels 3

EmS number F-E, <u>S-E</u>

**IATA** 

Packaging group III

Labels 3

14.5 Environmental hazards

**ADR** 

Environmentally hazardous yes

## SÜDWEST Super-Dickschutz Uni

**IMDG** 

Marine pollutant yes

14.6 Special precautions for user

Remarks This information is not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable

**Additional advice** 

ADR: Packages < 5 I: No dangerous goods (ADR

2.2.3.1.5).

IMDG: Packages < 5 I: No dangerous goods (IMDG

2.3.2.5).

#### **SECTION 15: REGULATORY INFORMATION**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

Directive 2010/75/EU 28,4 %

371,8 g/l

VOC

Directive 2004/42/EC 28,57 %

374,22 g/l

EU limit value for this product (cat. A/i) :500 g/IThis product

contains max500 g/IVOC.

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous

Not applicable

chemicals

Other regulations Comply with the statutory regulations on health and safety at

work.

Take note of Dir 94/33/EC on the protection of young people

at work.

Take note of Dir 92/85/EEC on the safety and health at work

of pregnant workers.

#### 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: OTHER INFORMATION**

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

#### **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H318 : Causes serious eye damage.

H336 : May cause drowsiness or dizziness.

H361d : Suspected of damaging the unborn child.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP -Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

# SÜDWEST Super-Dickschutz Uni

Department issuing MSDS REG\_EU / EN

sdb@suedwest.de