

## SAFETY DATA SHEET

# SÜDWEST 2K-Acryl-Seidenglanzlack

Ref.	130000006272/
Rev. no.	1.3
Revision Date	04.10.2018
Print Date	05.11.2018

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name SÜDWEST 2K-Acryl-Seidenglanzlack

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating compound/ Surface coating/ paint

Reserved for industrial and professional use.

Uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
Telefax: +49 6324/709-175  
www.suedwest.de

E-mail address of person responsible for the SDS  
European Union

sdb@suedwest.de

#### 1.4 Emergency telephone number European Union

Phone: +44 (0)1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids,  
Category 3

H226: Flammable liquid and vapour.

Skin irritation, Category 2

H315: Causes skin irritation.

# SÜDWEST 2K-Acryl- Seidenglanzlack

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity  
- single exposure, Category  
3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity  
- single exposure, Category  
3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity  
- repeated exposure,  
Category 2

H373: May cause damage to organs through prolonged  
or repeated exposure.

Long-term (chronic) aquatic  
hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Warning

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary  
statements

### Prevention:

P210 Keep away from heat, hot surfaces,

# SÜDWEST 2K-Acryl- Seidenglanzlack

P260 sparks, open flames and other ignition sources. No smoking.  
P280 Do not breathe vapours.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Disposal:**

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

Hazardous components which must be listed on the label:

xylene (mixture of isomers)  
Hydrocarbons, C9, aromatics

**Additional Labelling:**

EUH208 Contains Fatty acids, C14-18 and C16-18-unsatd., maleated. May produce an allergic reaction.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures**

Chemical nature Alkyd resin based paint.

**Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)

# SÜDWEST 2K-Acryl- Seidenglanzlack

xylene (mixture of isomers)	1330-20-7 215-535-7 01-2119488216-32-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 Asp. Tox.1; H304	≥ 20 - < 30
Hydrocarbons, C9, aromatics	64742-95-6  01-2119455851-35-XXXX	Asp. Tox.1; H304 Flam. Liq.3; H226 STOT SE3; H335, H336 Aquatic Chronic2; H411  Note H (Table 3.1), Note P The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 10 - < 20
Fatty acids, C14-18 and C16-18-unsatd., maleated	288-306-2 01-2119976378-19-XXXX	Skin Irrit.2; H315 Skin Sens.1; H317	≥ 0,1 - < 1

For explanation of abbreviations see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately.

# SÜDWEST 2K-Acryl- Seidenglanzlack

Wash skin thoroughly with soap and water or use recognized skin cleanser.

Do NOT use solvents or thinners.

If skin irritation persists, call a physician.

## Eye contact

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical advice.

## Ingestion

Rinse mouth with water.

If swallowed, seek medical advice immediately and show this container or label.

Keep at rest.

Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

### Symptoms

Liver disorders

Kidney disorders

Damage

Nervous system

Inhalation may provoke the following symptoms:  
irritant effects

Headache

Vertigo

Drowsiness

Unconsciousness

## 4.3 Indication of any immediate medical attention and special treatment needed

### Treatment

Treat symptomatically.

No information available.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

#### Suitable extinguishing media

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:

Carbon monoxide

Carbon dioxide (CO<sub>2</sub>)

Nitrogen oxides (NO<sub>x</sub>)

Exposure to decomposition products may be a hazard to health.

Cool closed containers exposed to fire with water spray.

# SÜDWEST 2K-Acryl- Seidenglanzlack

**5.3 Advice for  
firefighters**

In the event of fire, wear self-contained breathing apparatus.  
Fight fire with normal precautions from a reasonable  
distance.

**Additional advice**

Fire residues and contaminated fire extinguishing water  
must be disposed of in accordance with local regulations.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal  
precautions, protective  
equipment and  
emergency procedures**

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

**6.2 Environmental  
precautions**

The product should not be allowed to enter drains, water  
courses or the soil.  
If the product contaminates rivers and lakes or drains inform  
respective authorities.

**6.3 Methods and  
material for  
containment and  
cleaning up**

Contain spillage, and then collect with non-combustible  
absorbent material, (e.g. sand, earth, diatomaceous earth,  
vermiculite) and place in container for disposal according to  
local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to  
item 13.

**6.4 Reference to other  
sections**

Refer to protective measures listed in sections 7 and 8.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling****Advice on safe handling**

Comply with the statutory regulations on health and safety at  
work.  
Avoid formation of aerosol.  
Prevent the creation of flammable or explosive  
concentrations of vapour in air and avoid vapour  
concentration higher than the  
occupational exposure limit values.  
The product should only be used in areas from which all  
naked lights and other sources of ignition have been  
excluded.  
All metal parts of the mixing and processing equipment must  
be earthed.

# SÜDWEST 2K-Acryl- Seidenglanzlack

Operators should wear antistatic footwear and clothing. No sparking tools should be used.

## Hygiene measures

Do not breathe spray, vapour.  
Take off immediately all contaminated clothing.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
After washing hands, replenish lost skin oil by means of oily skin ointment.  
When using do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

### Requirements for storage areas and containers

Store in original container.  
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.  
Prevent unauthorized access.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a well-ventilated place.  
Protect from frost, heat and sunlight.

### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Keep away from sources of ignition - No smoking.  
Take measures to prevent the build up of electrostatic charge.

### Advice on common storage

Keep away from combustible materials.  
Keep away from food, drink and animal feedingstuffs.  
Keep away from oxidizing agents and strongly acid or alkaline materials.

## 7.3 Specific end use(s)

For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

xylene (mixture of isomers)	1330-20-7
2000/39/EC	Limit Value - eight hours 221 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours 50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin

# SÜDWEST 2K-Acryl- Seidenglanzlack

2000/39/EC	Indicative Short term exposure limit	442 mg/m <sup>3</sup>
2000/39/EC	Short term exposure limit	100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin	
	Indicative	

The lists that were valid during the creation were used as basis.

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

### Individual protection measures, such as personal protective equipment

a) Eye/face protection      Safety glasses with side-shields conforming to EN166

b) Skin protection

Hand protection

Recommended preventive skin protection  
Before starting work, apply water-resistant skincare preparations to exposed skin areas.  
Protective gloves should be worn in case of skin contact during preparation and application.

Break through time: 480 min

Minimum thickness: 0,4 mm

Gloves made of nitrile rubber, e.g. KCL 730 Camatril®

Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.

Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Body Protection

Preventive skin protection

Long sleeved clothing

Personal should wear antistatic clothings made of natural



# SÜDWEST 2K-Acryl- Seidenglanzlack

fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

## c) Respiratory protection

When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.  
Breathing protection equipment required in inadequately ventilated places and during spraying.  
In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.  
Combination filter A-P2  
Respiratory protection complying with EN 14387.

## Environmental exposure controls

### General advice

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	liquid
Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	not determined
Melting point/freezing point	No data available
Initial boiling point and boiling range	127 °C
Flash point	25 °C
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	7,0 %(V)

# SÜDWEST 2K-Acryl- Seidenglanzlack

Lower explosion limit / Lower flammability limit	0,6 %(V)
Vapour pressure	5 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,12 g/cm <sup>3</sup>
Solubility(ies) Water solubility	insoluble
Partition coefficient: n- octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity Viscosity, dynamic	ca. 130 mPa.s (40 °C)
Viscosity, kinematic	ca. 116,1 mm <sup>2</sup> /s (40 °C)
Explosive properties	Not explosive In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

## 9.2 Other information

Ignition temperature	370 °C
Flow time	> 90 s at 20 °C Cross section: 4 mm Method: ISO 2431

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

# SÜDWEST 2K-Acryl- Seidenglanzlack

Hazardous reactions      No dangerous reaction known under conditions of normal use.  
Vapours may form explosive mixture with air.

## 10.4 Conditions to avoid

Conditions to avoid      Direct sources of heat.  
Strong sunlight for prolonged periods.

## 10.5 Incompatible materials

Materials to avoid      Strong acids and strong bases  
Strong oxidizing agents

## 10.6 Hazardous decomposition products

Hazardous decomposition products      No decomposition if stored and applied as directed.  
Decomposition temperature      No data available

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity      Based on available data, the classification criteria are not met.

Acute inhalation toxicity      Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity      Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

#### **|| xylene (mixture of isomers):**

Acute inhalation toxicity      LC50 (Rat): 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity      Harmful in contact with skin.

#### **Skin corrosion/irritation**

##### Product:

Causes skin irritation.

# SÜDWEST 2K-Acryl- Seidenglanzlack

**Components:****|| xylene (mixture of isomers):**

Causes skin irritation.

**|| Hydrocarbons, C9, aromatics:**

Repeated exposure may cause skin dryness or cracking.

**|| Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Causes skin irritation.

**Serious eye damage/eye irritation****Product:**

Causes serious eye irritation.

**Components:****|| xylene (mixture of isomers):**

Causes serious eye irritation.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Components:****|| Fatty acids, C14-18 and C16-18-unsatd., maleated:**

May cause an allergic skin reaction.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

**Developmental Toxicity**

Based on available data, the classification criteria are not met.

# SÜDWEST 2K-Acryl- Seidenglanzlack

## STOT - single exposure

### Product:

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

### Components:

#### **|| xylene (mixture of isomers):**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

#### **|| Hydrocarbons, C9, aromatics:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

## STOT - repeated exposure

### Product:

Assessment

May cause damage to organs through prolonged or repeated exposure.

### Components:

#### **|| xylene (mixture of isomers):**

Assessment

May cause damage to organs through prolonged or repeated exposure.

## Aspiration toxicity

### Product:

Based on available data, the classification criteria are not met.

### Components:

#### **|| xylene (mixture of isomers):**

May be fatal if swallowed and enters airways.

#### **|| Hydrocarbons, C9, aromatics:**

May be fatal if swallowed and enters airways.

## Experience with human exposure

### Product:

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.  
Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

# SÜDWEST 2K-Acryl- Seidenglanzlack

**xylene (mixture of isomers) :**

Partition coefficient: n-  
octanol/water log Pow: > 3

**12.4 Mobility in soil****Product:**

Mobility No data available

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects****Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems. Harmful to aquatic life with long lasting effects.

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Product	The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Partial and residual quantities can be reused. Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.
Contaminated packaging	Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
Waste key for the unused product	08 01 11* Paint and varnish waste containing organic solvents or other dangerous substances

# SÜDWEST 2K-Acryl- Seidenglanzlack

(\*) hazardous waste in terms of the European directive  
91/689/EEC

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number

ADR	1263
IMDG	1263
IATA	1263

### 14.2 UN proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

### 14.3 Transport hazard class(es)

ADR	3
IMDG	3
IATA	3

### 14.4 Packing group

ADR	
Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)
IMDG	
Packaging group	III



# SÜDWEST 2K-Acryl- Seidenglanzlack

Labels 3  
EmS number F-E, S-E

## IATA

Packaging group III  
Labels 3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous no

### IMDG

Marine pollutant no

## 14.6 Special precautions for user

Remarks This information is not available.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable

## Additional advice

ADR ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5)  
IMDG IMDG: Packages < 30l: No dangerous goods (IMDG 2.3.2.5).

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU 53 %  
594 g/l

# SÜDWEST 2K-Acryl- Seidenglanzlack

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No  
649/2012 of the European  
Parliament and the Council  
concerning the export and  
import of dangerous  
chemicals

Not applicable

Other regulations

Comply with the statutory regulations on health and safety at work.

Take note of Dir 94/33/EC on the protection of young people at work.

Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

## 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.

# SÜDWEST 2K-Acryl- Seidenglanzlack

H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.

## Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -

# SÜDWEST 2K-Acryl- Seidenglanzlack

Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing  
MSDS  
REG\_EU / EN

sdb@suedwest.de

# **SÜDWEST 2K-Acryl- Seidenglanzlack**