

SÜDWEST Dachbeschichtung

Ref.13Rev. no.1Revision Date30Print Date1

13000006192/ 1.3 30.10.2018 11.01.2019

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier Trade name	SÜDWEST Dachbeschichtung
1.2 Relevant identified uses of the substance or mixture and uses advised against	Coating compound/ Surface coating/ paint
Uses advised against	This information is not available.
1.3 Details of the supplier of the safety data sheet	SÜDWEST Lacke + Farben GmbH & Co.KG Iggelheimer Str. 13 D - 67459 Böhl-Iggelheim Telephone: +49 6324/709-0 Telefax: +49 6324/709-175 www.suedwest.de
E-mail address of person responsible for the SDS European Union	sdb@suedwest.de
1.4 Emergency telephone number European Union	Phone: +44 (0)1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic H412: Harmful to aquatic life with long lasting effects. hazard, Category 3

SÜDWEST Dachbeschichtung

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	Prevention: P273 Disposal:	Avoid release to the environment.
	P501	Contents/container to be disposed of

Additional Labelling:

EUH208

Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2Hisothiazol-3-one. May produce an allergic reaction. For 2-Methyl-2H-Isothiazol-3-one (MIT), a labelling threshold of 15 ppm is voluntarily used in accordance with the CEPE recommendation (instead of 100 ppm).

through approved disposal contractor or taken to municipal collection point.

Regulation concerning biocidal products (528/2012):

Contains Terbutryn , 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. As active agents for coating and storage protection in accordance with Biocidal Product Regulation (528/2012), Article 58(3)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%
	EC-No.	(REGULATION (EC)	w/w)
	Registration number	No 1272/2008)	

SÜDWEST Dachbeschichtung

Terbutryn	886-50-0 212-950-5	Acute Tox.4; H302 Skin Sens.1B; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	≥ 0,0025 - < 0,025
1,2-benzisothiazol- 3(2H)-one	2634-33-5 220-120-9	Acute Tox.4; H302 Skin Irrit.2; H315 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Acute1; H400	< 0,05

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.	
Inhalation	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.	
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.	
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.	
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.	
4.2 Most important symptoms and effects, both acute and delayed		
Symptoms	No information available.	

SÜDWEST Dachbeschichtung

4.3 Indication of any immediate medical attention and special treatment needed

Treatment

Treat symptomatically. No information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray
Unsuitable extinguishing media	High volume water jet
5.2 Special hazards arising from the substance or mixture	Fire may cause evolution of: Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx) Exposure to decomposition products may be a hazard to health.
5.3 Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.
Additional advice	Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
SECTIO	ON 6: ACCIDENTAL RELEASE MEASURES
6.1 Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Do not breathe vapour.
6.2 Environmental precautions	The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents. Dispose of contaminated material as waste according to

Clean contaminated surface thoroughly.

item 13.

SÜDWEST Dachbeschichtung

6.4 Reference to other Refer to protective measures listed in sections 7 and 8. **sections**

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling	Avoid contact with skin and eyes. Prevent unauthorized access. Provide sufficient air exchange and/or exhaust in work rooms. Comply with the statutory regulations on health and safety at work.
Hygiene measures	Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Observe label precautions. Protect from frost, heat and sunlight.
Advice on common storage	Keep away from oxidizing agents and strongly acid or alkaline materials.
7.3 Specific end use(s)	For further information, see also Technical Data Sheet for the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

SÜDWEST Dachbeschichtung

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

a) Eye/face protection	Wear protective goggles for protection against splashed liquid.
	Safety glasses with side-shields conforming to EN166
b) Skin protection Hand protection	Recommended preventive skin protection Before starting work, apply water-resistant skincare preparations to exposed skin areas. Protective gloves should be worn in case of skin contact during preparation and application.
	Break through time: 480 min Minimum thickness: 0,4 mm Gloves made of nitrile rubber,e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659- 87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.
	The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Body Protection	Work clothes Skin should be washed after contact. Do NOT use solvents or thinners.
c) Respiratory protection	No personal respiratory protective equipment normally required. In case of insufficient ventilation, wear suitable respiratory equipment. Employees involved in spraying work or in the immediate vicinity of such work should use a P2 particle filter against spray fog. Respiratory protection complying with EN 143.

Environmental exposure controls

General advice	The product should not be allowed to enter drains, water
	courses or the soil.

SÜDWEST Dachbeschichtung

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	liquid
Colour	various
Odour	characteristic
Odour Threshold	No data available
рН	ca. 8,9
Melting point/freezing point	No data available
Initial boiling point and boiling range	100 °C
Flash point	Not applicable
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Vapour pressure	23 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,437 g/cm ³
Solubility(ies) Water solubility	partly miscible
Partition coefficient: n- octanol/water	not determined
Auto-ignition temperature	not auto-flammable

SÜDWEST Dachbeschichtung

Viscosity Viscosity, dynamic	ca. 6.554 mPa.s (20 °C)
Viscosity, kinematic	No data available
Explosive properties	Not explosive
Oxidizing properties	Not applicable
9.2 Other information	

Flow time

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions This information is not available.

10.4 Conditions to avoid

Conditions to avoid Stable under recommended storage and handling conditions (see section 7).

10.5 Incompatible materials

Materials to avoid	Strong acids and strong bases
	Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition No decomposition if stored and applied as directed. products

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effectsAcute toxicityProduct:Acute oral toxicityBased on av

Based on available data, the classification criteria are not met.

SÜDWEST Dachbeschichtung

Acute inhalation toxicity	Based on available data, the classification criteria are not met.
Acute dermal toxicity	Based on available data, the classification criteria are not met.
<u>Components:</u> Terbutryn: Acute oral toxicity	Harmful if swallowed.
1,2-benzisothiazol-3(2H)-one Acute oral toxicity	: Harmful if swallowed.
Skin corrosion/irritation <u>Product:</u>	Based on available data, the classification criteria are not met.
<u>Components:</u> 1,2-benzisothiazol-3(2H)-one	: Causes skin irritation.
Serious eye damage/eye irrit Product:	ation
	Based on available data, the classification criteria are not met.
<u>Components:</u> 1,2-benzisothiazol-3(2H)-one	: Causes serious eye damage.
Respiratory or skin sensitisa	tion
Product:	Based on available data, the classification criteria are not met.
<u>Components:</u> Terbutryn: Species Method	Mouse OECD Test Guideline 429
1,2-benzisothiazol-3(2H)-one	May cause an allergic skin reaction.
.,	-

May cause an allergic skin reaction.

SÜDWEST Dachbeschichtung

Germ cell mutagenicity

Product:

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

Carcinogenicity Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity Product: Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure <u>Product:</u>

Based on available data, the classification criteria are not met.

STOT - repeated exposure Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity <u>Product:</u> Based on available data, the classification criteria are not met.

Further information <u>Product:</u>

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product:

Toxicity to fish

No data available

Components:

SÜDWEST Dachbeschichtung

Terbutryn :

M-Factor (Short-term (acute) aquatic hazard)	100
Toxicity to bacteria	EC20 (activated sludge): > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209
M-Factor (Long-term (chronic) aquatic hazard)	100
1,2-benzisothiazol-3(2H)-one	9:
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 1,6 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia (water flea)): 2,94 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Short-term (acute) aquatic hazard)	1
Toxicity to bacteria	EC50 (Pseudomonas putida): 0,4 mg/l Exposure time: 16 h

12.2 Persistence and degradability

Product:

o data available

<u>Components:</u> Terbutryn :

reibuti yn .	
Biodegradability	Inoculum: activated sludge
	Result: not rapidly degradable
	Biodegradation: 0 %
	Method: OECD Test Guideline 301F

1,2-benzisothiazol-3(2H)-one :

-	• •	
Biodegradability		Result: rapidly degradable
		Biodegradation: > 90 %
		Method: OECD Test Guideline 303A

SÜDWEST Dachbeschichtung

12.3 Bioaccumulative potential

Product:

Bioaccumulation	No data available

Components:

Bioaccumulation	Bioconcentration factor (BCF): 103 Method: Calculation method	

Partition coefficient: noctanol/water log Pow: 3,19Method: OECD Test Guideline 117

1,2-benzisothiazol-3(2H)-one :

Partition coefficient: n- log Pow: 0,4 octanol/water

12.4 Mobility in soil

Product:

Mobility

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological	Do not allow product to enter into ground water, bodies
information	of water or sewage systems. Harmful to aquatic life with
	long lasting effects.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations. Partial and residual quantities can be reused.

SÜDWEST Dachbeschichtung

Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
08 01 11* Paint and varnish waste containing organic solvents or other dangerous substances
(*) hazardous waste in terms of the European directive 91/689/EEC

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks

This information is not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks

Not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SÜDWEST Dachbeschichtung

VOC

Directive 2010/75/EU	
----------------------	--

2,1 % 30,1 g/l

VOC Directive 2004/42/EC 2,1 % 30,1 g/l

EU limit value for this product (cat. A/i) :140 g/IThis product contains max140 g/IVOC.

Other regulations

Comply with the statutory regulations on health and safety at work.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. :	Acute toxicity
Aquatic Acute :	Short-term (acute) aquatic hazard
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Eye Dam. :	Serious eye damage
Skin Irrit. :	Skin irritation
Skin Sens. :	Skin sensitisation

1907/2006

SAFETY DATA SHEET

SÜDWEST Dachbeschichtung

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP -Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS REG EU/EN

sdb@suedwest.de

SÜDWEST Dachbeschichtung